

## Pneumatic Hog Ring Tool

### Type HC716

**Description:**

The HC716 hog ring tool takes KHF 16110 series hog rings available in materials from bright, galvanized and stainless. The relatively low air consumption allows for use with standard compressors. The tool is designed for long service life and easy maintenance through careful engineering. Benefits of using this tool can be seen immediately in less man hours on the job, lower occurrences of installer injuries and lower per connection prices.



**Popular applications:**

Automotive Seating, Commercial Fence Installation, Bag Closure, Oil Absorption Socks, Crafts, Erosion Control, Construction, Bedding

<b>Length:</b>	12.75 inches (323.00mm)
<b>Height:</b>	8.66 inches (220.00mm)
<b>Width:</b>	3.66 inches ( 93.00mm)

Technical Data	
Type description:	<b>HC716 Long Magazine</b>
Article code:	HRT960009
Magazine type:	Rear loading
Staple type:	16110 Series
Magazine capacity:	110
Fasteners per strip:	1 x 110
Operating pressure:	95 psi (0.66 Nmm <sup>2</sup> )
Max. operating pressure:	100 psi (0.69 Nmm <sup>2</sup> )
Air consumption/operation:	3.2 cu. inch (0.08 cu. meter)
Inner hose diam. required:	3/8" (9.5mm) Ø recommended
Emission sound level at the workstation:	d = 82 dB
Weight:	3.00 lbs. (1.361 kg)
Extras supplied with the tool:	Operators manual, spare parts list, service instructions. For safety reasons we recommend that your operators read and understand all safety precautions prior to operating the tool.

**Accessories:**

Article code	Description
P960009	3/4" Hog Rings (available in variety of materials)
All KHF pneumatic tools can be jig-mounted. We supply the necessary accessories and equipments.	
	